
































**A CLASS CARRIAGE** **XR5919** **COMPACT BOOM** **B CLASS CARRIAGE** **XR842** **HIGH PIVOT ROLLER BOOM** **B CLASS CARRIAGE** **XR1045** **HIGH PIVOT ROLLER BOOM** **B CLASS CARRIAGE** **XR1055** **HIGH PIVOT ROLLER BOOM** **B CLASS CARRIAGE** **XR1245** **HIGH PIVOT ROLLER BOOM** **B CLASS CARRIAGE** **XR1255** **HIGH PIVOT ROLLER BOOM** **B CLASS CARRIAGE** **XR1270** **HIGH PIVOT ROLLER BOOM** **C CLASS CARRIAGE** **XR1534** **HIGH CAPACITY ROLLER BOOM**

<p><b>5,900 LBS CAPACITY</b> <b>19 FT LIFT HEIGHT</b> <b>74 HP</b></p>  <p>Capacity: 5,900 lbs Max. Lift Height: 19' Forward Reach: 11' Frame Leveling L/R: N/A Weight: 11,200 lbs Engine: (Deutz 2.9L) 74 hp Fuel Capacity: 17 gal Tires: 12.00 x 16.5 pneumatic GPM: 26 PSI: 3,500 Hydraulic Oil Cap: 24 gal Length to fork face: 12' 8" Width: 71" Height: 6' 7" Wheel Base: 93" Ground Clearance: 10.8" Turning Radius: 11' Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE</b></p> 	<p><b>8,000 LBS CAPACITY</b> <b>42 FT LIFT HEIGHT</b> <b>74 HP HT</b> <b>OPTIONAL 120 HP</b></p>  <p>Capacity: 8,000 lbs Max. Lift Height: 42' Forward Reach: 28' 11" Frame Leveling L/R: 11° Weight: 28,460 lbs Engine: (Cummins 3.8L) 74 hp HT Fuel Capacity: 48 gal Tires: Foam Filled 13.00 x 24 GPM: 39 PSI: 3,500 Hydraulic Oil Cap: 58 gal Length to fork face: 20' 9" Width: 101" Height: 8' 1" Wheel Base: 120" Ground Clearance: 16.5" Turning Radius: 12' Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE</b></p> 	<p><b>10,000 LBS CAPACITY</b> <b>45 FT LIFT HEIGHT</b> <b>74 HP HT</b> <b>OPTIONAL 120 HP</b></p>  <p>Capacity: 10,000 lbs Max. Lift Height: 45' Forward Reach: 30' 4" Frame Leveling L/R: 11° Weight: 30,610 lbs Engine: (Cummins 3.8L) 74 hp HT Fuel Capacity: 48 gal Tires: Foam Filled 13.00 x 24 GPM: 49 PSI: 3,500 Hydraulic Oil Cap: 58 gal Length to fork face: 21' 3" Width: 101" Height: 8' 1" Wheel Base: 120" Ground Clearance: 16.5" Turning Radius: 12' Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE</b></p> 	<p><b>10,000 LBS CAPACITY</b> <b>55 FT LIFT HEIGHT</b> <b>74 HP HT</b> <b>OPTIONAL 120 HP</b></p>  <p>Capacity: 10,000 lbs Max. Lift Height: 55' Forward Reach: 40' 7" Frame Leveling L/R: 11° Weight: 34,000 lbs Engine: (Cummins 3.8L) 74 hp HT Fuel Capacity: 50 gal Tires: Foam Filled 14x28 GPM: 49 PSI: 3,500 Hydraulic Oil Cap: 62 gal Length to fork face: 22' 2" Width: 102" Height: 8' 1" Wheel Base: 125" Ground Clearance: 17.75" Turning Radius: 12' 2" Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE (OUTRIGGERS DOWN)</b></p> 	<p><b>12,000 LBS CAPACITY</b> <b>45 FT LIFT HEIGHT</b> <b>120 HP</b></p>  <p>Capacity: 12,000 lbs Max. Lift Height: 45' Forward Reach: 30' 4" Frame Leveling L/R: 11° Weight: 34,380 lbs Engine: (Cummins 3.8L) 120 hp Fuel Capacity: 48 gal Tires: Foam Filled 16 x 25 GPM: 49 PSI: 3,500 Hydraulic Oil Cap: 58 gal Length to fork face: 22' 2" Width: 102" Height: 8' 1" Wheel Base: 124" Ground Clearance: 16.5" Turning Radius: 12' 2" Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE (OUTRIGGERS DOWN)</b></p> 	<p><b>12,000 LBS CAPACITY</b> <b>55 FT LIFT HEIGHT</b> <b>120 HP</b></p>  <p>Capacity: 12,000 lbs Max. Lift Height: 55' Forward Reach: 38' Frame Leveling L/R: 11° Weight: 36,420 lbs Engine: (Cummins 3.8L) 120 hp Fuel Capacity: 48 gal Tires: Foam Filled 15.5 x 25 GPM: 49 PSI: 3,500 Hydraulic Oil Cap: 58 gal Length to fork face: 24' 8" Width: 102" Height: 8' 1" Wheel Base: 141" Ground Clearance: 15" Turning Radius: 14' Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE (OUTRIGGERS DOWN)</b></p> 	<p><b>12,000 LBS CAPACITY</b> <b>70 FT LIFT HEIGHT</b> <b>134 HP</b></p>  <p>Capacity: 12,000 lbs Max. Lift Height: 70' Forward Reach: 53' 10" Frame Leveling L/R: 8° Weight: 47,100 lbs Engine: (Deutz 3.6L) 134 hp Fuel Capacity: 72 gal Tires: Foam Filled 17.5 x 25 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 26' 6" Width: 102" Height: 8' 1" Wheel Base: 147" Ground Clearance: 15" Turning Radius: 12' 2" Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE (OUTRIGGERS DOWN)</b></p> 	<p><b>15,000 LBS CAPACITY</b> <b>34 FT LIFT HEIGHT</b> <b>120 HP</b></p>  <p>Capacity: 15,000 lbs Max. Lift Height: 34' Forward Reach: 17' Frame Leveling L/R: 11° Weight: 32,480 lbs Engine: (Cummins 3.8L) 120 hp Fuel Capacity: 48 gal Tires: Foam Filled 15.5 x 25 GPM: 49 PSI: 4,300 Hydraulic Oil Cap: 58 gal Length to fork face: 22' Width: 102" Height: 8' 1" Wheel Base: 124" Ground Clearance: 16.5" Turning Radius: 12' 2" Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE</b></p> 
---	--	---	--	--	--	--	--

<p><b>C CLASS CARRIAGE</b> <b>XR2034</b> <b>HIGH CAPACITY ROLLER BOOM</b></p>  <p><b>20,000 LBS CAPACITY</b> <b>34 FT LIFT HEIGHT</b> <b>134 HP</b></p> <p>Capacity: 20,000 lbs Max. Lift Height: 34' Forward Reach: 16' 7" Frame Leveling L/R: 8° Weight: 40,150 lbs Engine: (Deutz 3.6L) 134 hp Fuel Capacity: 72 gal Tires: Foam Filled 17.5 x 25 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 26' 1" Width: 102" Height: 8' 11" Wheel Base: 147" Ground Clearance: 15" Turning Radius: 15' 10" Warranty: Xtreme 10-5-2</p> <p><b>FORK POSITIONING CARRIAGE</b></p> 	<p><b>C CLASS CARRIAGE</b> <b>XR2042</b> <b>HIGH CAPACITY ROLLER BOOM</b></p>  <p><b>20,000 LBS CAPACITY</b> <b>42 FT LIFT HEIGHT</b> <b>134 HP</b></p> <p>Capacity: 20,000 lbs Max. Lift Height: 42' Forward Reach: 24' 10" Frame Leveling L/R: 8° Weight: 41,000 lbs Engine: (Deutz 3.6L) 134 hp Fuel Capacity: 72 gal Tires: Foam Filled 17.5 x 25 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 26' 1" Width: 102" Height: 8' 11" Wheel Base: 147" Ground Clearance: 15" Turning Radius: 15' 10" Warranty: Xtreme 10-5-2</p> <p><b>FIXED CARRIAGE</b></p> 	<p><b>C CLASS CARRIAGE</b> <b>XR2045</b> <b>HIGH CAPACITY ROLLER BOOM</b></p>  <p><b>20,000 LBS CAPACITY</b> <b>45 FT LIFT HEIGHT</b> <b>134 HP</b></p> <p>Capacity: 20,000 lbs Max. Lift Height: 45' Forward Reach: 27' 4" Frame Leveling L/R: 8° Weight: 44,750 lbs Engine: (Deutz 3.6L) 134 hp Fuel Capacity: 72 gal Tires: Foam Filled 17.5 x 25 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 22' 6" Width: 102" Height: 8' 11" Wheel Base: 148" Ground Clearance: 15" Turning Radius: 15' 10" Warranty: Xtreme 10-5-2</p> <p><b>FORK POSITIONING CARRIAGE (OUTRIGGERS DOWN)</b></p> 	<p><b>D CLASS CARRIAGE</b> <b>XR2450</b> <b>ULTRA HIGH CAPACITY ROLLER BOOM</b></p>  <p><b>24,000 LBS CAPACITY</b> <b>50 FT LIFT HEIGHT</b> <b>173 HP</b></p> <p>Capacity: 24,000 lbs Max. Lift Height: 50' Forward Reach: 36' Frame Leveling L/R: 8° Weight: 52,500 lbs Engine: (Cummins 4.5L) 173 hp Fuel Capacity: 72 gal Tires: Foam Filled 16.00 x 25 - 28 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 28' Width: 102" Height: 9' 6" Wheel Base: 148" Ground Clearance: 15" Turning Radius: 16' 8" Warranty: Xtreme 10-5-2</p> <p><b>FORK POSITIONING CARRIAGE (OUTRIGGERS DOWN)</b></p> 	<p><b>D CLASS CARRIAGE</b> <b>XR3034</b> <b>ULTRA HIGH CAPACITY ROLLER BOOM</b></p>  <p><b>30,000 LBS CAPACITY</b> <b>34 FT LIFT HEIGHT</b> <b>173 HP</b></p> <p>Capacity: 30,000 lbs Max. Lift Height: 34' Forward Reach: 17' 6" Frame Leveling L/R: 8° Weight: 47,850 lbs Engine: (Cummins 4.5L) 173 hp Fuel Capacity: 72 gal Tires: Foam Filled 16.00 x 25 - 28 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 23' 11" Width: 102" Height: 9' 6" Wheel Base: 148" Ground Clearance: 18" Turning Radius: 16' 8" Warranty: Xtreme 10-5-2</p> <p><b>FORK POSITIONING CARRIAGE</b></p> 	<p><b>E CLASS CARRIAGE</b> <b>XR4030</b> <b>XTREME CAPACITY ROLLER BOOM</b></p>  <p><b>40,000 LBS CAPACITY</b> <b>30 FT LIFT HEIGHT</b> <b>173 HP</b></p> <p>Capacity: 40,000 lbs Max. Lift Height: 30' Forward Reach: 16' 4" Frame Leveling L/R: 8° Weight: 63,000 lbs Engine: (Cummins 4.5L) 173 hp Fuel Capacity: 72 gal Tires: Foam Filled 23.5 R29 GPM: 49 PSI: 4,000 Hydraulic Oil Cap: 58 gal Length to fork face: 21' 8" Width: 102" Height: 9' 10" Wheel Base: 148" Ground Clearance: 18" Turning Radius: 21' 11" Warranty: Xtreme 10-5-2</p> <p><b>FORK POSITIONING CARRIAGE</b></p> 	<p><b>F CLASS CARRIAGE</b> <b>XR7038</b> <b>ULTRA XTREME CAPACITY ROLLER BOOM</b></p>  <p><b>70,000 LBS CAPACITY</b> <b>38 FT LIFT HEIGHT</b> <b>300 HP</b></p> <p>Capacity: 70,000 lbs Max. Lift Height: 38' 2" Forward Reach: 22' Frame Leveling L/R: 7° Weight: 115,000 lbs Engine: (Cummins 9L) 300 hp Fuel Capacity: 150 gal Tires: Foam Filled 29.5 R29 GPM: 92 PSI: 4,200 Hydraulic Oil Cap: 140 gal Length to fork face: 27' 9" Width: 117" Height: 11' 7" Wheel Base: 188" Ground Clearance: 20.5" Turning Radius: 24' 6" Warranty: Xtreme 10-5-2</p> <p><b>FORK POSITIONING CARRIAGE</b></p> 
--	--	--	--	---	---	---

**XTREME SERVICE & SUPPORT**


All Xtreme telehandlers are backed by our industry-leading 10 year - 5 year - 2 year warranty. For technical support or spare parts, our nationwide network of over 90 sales and service locations are ready to assist.



**10-5-2 WARRANTY**  
10 YEARS OF 10,000 HOURS FRAME & CHASSIS WELDMET  
5 YEARS OF 5,000 HOURS BOOM WELDMET & ROLLERS  
2 YEARS OF 2,000 HOURS ENGINE, ELECTRICAL, TRANSMISSION, DRIVE AXLES & HYDRAULIC COMPONENTS

**EZ LOADER**  
CUSTOM DELIVERY TRUCK BEDS  
**LOADING MADE EASY**

- BULKHEAD BOLTED TO FRAME
- TRACTION PLATE FULL RAMP
- 17 SECOND RAMP DEPLOYMENT
- DOCK LOADING ABILITY



CAPACITIES	EZ12	EZ18	EZ24
Bed Capacity	12,000 lbs (5,443kg)	18,000 lbs (8,165kg)	24,000 lbs (10,886kg)
Dove Tail Load Capacity	8,000 lbs (3,628kg)	10,000 lbs (4,535kg)	15,000 lbs (6,803kg)
Top Capacity	5,000 lbs (2,267kg)	5,000 lbs (2,267kg)	10,000 lbs (4,535kg)
Approximate G.V.W.	26,000 lbs (11,793kg)	33,000 lbs (14,968kg)	48,000 lbs (21,772kg)
Hydraulic Pump P.T.O.	14 GPM (53 LPM)	14 GPM (53 LPM)	14 GPM (53 LPM)

DIMENSIONS	EZ12	EZ18	EZ24
Overall Bed W/L	8'6" (2.6m) W x 21'3" (6.4m) L	8'6" (2.6m) W x 25'3" (7.6m) L	8'6" (2.6m) W x 27'6" (8.3m) L
Main Bed W/L	8'6" (2.6m) W x 13'5" (4.1m) L	8'6" (2.6m) W x 17' (5.1m) L	8'6" (2.6m) W x 17'3" (5.2m) L
Dove Tail W/L	8'6" (2.6m) W x 7'5" (2.2m) L	8'6" (2.6m) W x 8' (2.4m) L	8'6" (2.6m) W x 10' (3m) L
Flip Tail W/L	8'6" (2.6m) W x 17' (5.1m) L	8'6" (2.6m) W x 9'3" (2.8m) L	8'6" (2.6m) W x 9'3" (2.8m) L
Bulk Head Height	5' (1.52m)	5' (1.52m)	5' (1.52m)
Cab to Aisle Length	11' 8" (3.5m)	15' 5" (4.7m)	13' 8" (4.1m)
Ramp Length	11'11" (3.5m)	13'4" (4.06m)	14'9" (4.5m)
Bed Height	3' 5" (1.04m)	3' 10" (1.16m)	4' (1.22m)
Max Dock Height	5' 5" (1.65m)	5' 8" (1.67m)	6' 3" (1.9m)
Ramp Degree/%	18/32%	18/32%	15/27%
Hitch Receiver Tube	2" (50.8mm)	2" (50.8mm)	2" (50.8mm)
Wood Thickness	1" (25.4mm)	1" (25.4mm)	1" (25.4mm)

Warranty (Bed Only) **1 Year All Components / 3 Year Structural**  
Note: Dimensions may change depending on truck manufacturer and model.

[www.xmfg.com/ez-loaders](http://www.xmfg.com/ez-loaders)



**THE XTREME DIFFERENCE.**  
IT'S MORE THAN JUST A PHRASE.

**Long Life Boom Rollers**

Rollers eliminate chatter, delivering smoother boom operation



**360° Visibility**

Operator can view the entire working area around the telehandler



**10-5-2 WARRANTY**

**10 YEARS OR 10,000 HOURS**  
FRAME & CHASSIS WELDMENT

**5 YEARS OR 5,000 HOURS**  
BOOM WELDMENT & ROLLERS

**2 YEARS OR 2,000 HOURS**  
ENGINE, ELECTRICAL, TRANSMISSION,  
DRIVE AXLES & HYDRAULIC COMPONENTS

**Boom Lift Point**

For safer handling of suspended loads



**Intuitive Operator Controls**

Function boom and chassis sway controls with one arm



**IT'S WHO WE ARE AND WHAT WE DO.**

Xtreme Manufacturing offers the largest range of heavy-duty and high capacity telehandlers in North America. Designed to outlast and outperform anything else in the industry, Xtreme has set the standard for safety, productivity and reliability, backed by a leading 10 year - 5 year - 2 year warranty.

Low maintenance, long-life boom rollers deliver smooth handling operation and lower total ownership costs, thanks to minimal downtime across the life of the machine. Other key Xtreme differences include 360 degree operator visibility from the cab, an integrated boom lift point for handling suspended loads, and intuitive controls that permit one hand on the steering wheel at all times.

\*Standard features may vary across individual models. Consult your sales representative for more details.

**STANDARD FEATURES**

- Long Life Boom Rollers
- 360° Visibility
- Boom Lift Point
- Intuitive Operator Controls Standard
- Auxiliary Hydraulics
- Solid Steel Plate Chassis
- Steel Dash
- Ductile Steel Manifold
- Easy Cab Mounted Grab Handles
- Reliable Tier 4 Compliant Engines
- Master Disconnect Switch
- Axle Mounted Outriggers
- Wider Outrigger Stance
- Large Cross Section Boom
- Easy Tie Downs
- "Y" Frame Sway Handle
- Heavy Duty Pre-Cleaner
- Additional High Pressure Hydraulic Filter
- Direct Engine/Trans Connection
- Individual Gauges and Switches
- Suspension Seat
- Easy Service Access
- Protected Tilt & Extend Cylinders
- Steel Hydraulic & Fuel Tanks
- Long Life Lexan Labels
- Heavy Duty Boom Chains
- Suspended Pedals
- Electrical Ring Terminals
- Large Capacity Fuel Tanks
- Trunnion Mounted Sway Cylinders
- Melanite Pins
- Rear Axle Stabilization (RAS)
- Center Mounted Power Train

**CAB, TIRES, CARRIAGES, & ATTACHMENTS**



**CAB OPTIONS**

All Xtreme telehandlers are available with a choice of open cab, enclosed cab, or enclosed cab with heat and air conditioning.

Please speak with your Xtreme sales representative for more details.

**TIRE OPTIONS**



**G2 FOAM FILLED**

Offers great tread depth, the G2 clears debris for improved traction.



**E3 FOAM FILLED**

Provide great traction and stability when run either off-road or on hard surfaces.



**XTREME SOLID TIRE**

The Xtreme solid tires provide a stable, cushioned, flat proof ride that is essential for both safety and productivity.

**FIXED CARRIAGE**

Floating forks and adjustable side-to-side for efficient load entry and exit.

- Range from 48" to 96"



**SWING CARRIAGE**

Allows for greater versatility in moving and placing materials in confined areas or when exact positioning is required.

- Range from 52" to 72"



**SIDE SHIFT CARRIAGE**

Four-inch left and right carriage shift allows for precision load placement.

- Range from 48" to 96"



**ADJUSTABLE CARRIAGE**

Fork positioning provides the ability to adjust the position of the forks, allowing the operator to handle a variety of loads without having to leave the cab.

- Range from 48" to 111"



**SIDE TILT CARRIAGE**

Tilts loads from side-to-side and allows for minor lateral positioning of the load during final placement.

- Range from 48" to 72"



**PIPE & POLE GRAPPLE**

Designed for handling multiple pipes or larger single pipe.

- Range from 72" to 96"
- Available with and without shoe



**PALLET FORK**

Rugged fork design makes it easier to handle heavy palletized material.



**LUMBER FORK**

Wide forks provide a larger surface area for stability for transporting larger materials.



**CUBING FORK**

Allows operator to handle cubes of brick and block with ease.



**PERSONNEL PLATFORM**

Extend the capabilities of your Xtreme telehandler by lifting personnel and materials.

- Range from 4'x4' to 8'x8'



**TRUSS BOOM**

Allows operator to set trusses and wall sections for wood and steel building construction.

- Range from 3' to 15'
- Available with and without winch



**SLING MOUNT**

Provides ability to handle suspended loads. Pick and tilt for precise load placement.



**PINTEL HOOK**


Versatile tow point for movement of equipment and material.



**GENERAL PURPOSE BUCKET**

Material bucket to carry loose dirt and materials and debris. The bucket can also be used for clean up around the job site.

- Range from 1.00yd to 2.00yd
- Available with or without Bolt on cutting edge



**GRAPPLE BUCKET**

Features a hydraulic grapple arm to secure bulky loads and assist in job site cleanup.



**TIRE MANIPULATOR**

Designed for the safe installation and removal of wheel assemblies from large construction and mining equipment, the fully integrated attachment utilizes Xtreme's existing in-cab controls for safe and seamless operation. The tire manipulator attachment is available to fit Xtreme telehandler models XR1045 and larger.



**ROTOBEC**

This pipe and pole grapple is used for vertical and horizontal material placement. It is a safe and efficient alternative for handling installation of everything from utility poles to gas pipelines.



From general construction to industrial applications, we offer the largest and most complete line of telehandlers in North America that is safer, more reliable, more productive, and proven to out last and outlast anything else in our industry. **Forget ordinary. Think Xtreme.**

Not all attachments are available for all models. Please check with your Xtreme sales representative at time of ordering.

XTREME MANUFACTURING, LLC  
8350 Eastgate Rd. Henderson, NV 89015  
p: 702.636.2969 or toll free: 800.497.1704  
[www.xmfg.com](http://www.xmfg.com)



**XR1270**

THE WORLDS TALLEST  
**FIXED BOOM TELEHANDLER**  
WITH  
**70' LIFT HEIGHT**

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to the appropriate Xtreme operation manual for detailed instructions on proper use, specifications, and maintenance of equipment.